



Intelligent Transport Systems

Type Approval

Certificate No:

ITS-TAN000056

Issued to:

A1 Roadlines Pty Ltd

For:

Illuminated Flashing Arrow Signs

Illuminated Flashing Arrow Signs			
RMS Specification:	FAS/5	Version:	1.0

Summary Scope:

Model: Type – A Arrow board Single-Sided

Model Number: Type A

Arrow Controller: QS-AB04

Software: 0721

Note: Conditions of approval are on the reverse side of this certificate.

Evaluation Reference:	ITS-EV00112	Approver:	Manager TSI
Approver Signature:	<i>Raj J Roychowdhry</i>	Date:	03/12/2018

A) Description and itemisation of the equipment covered by the type approval:

LED flashing arrow sign – type ‘A’ (models: single-sided Type A), comprising:

- Black sign board with thirteen (small element) 100mm High Intensity LED lamps (LED Lamp PCB model: LampAB with 32 LEDs) and visors on the front panel;
- LED lamp optical chamber ingress protection rating – IP65;
- Dimming control of LED lamps intensity using a photocell (light sensor firmware – 8169);
- Arrow controller (models: QS-AB04);
- 12V and 24V input power capability with a fuse;
- Sign board ingress protection rating – IP45;
- Electric actuator for raising and lowering of sign board.

B) Summary of deviations from specified requirements:

Nil.

C) Relevant Specifications, Drawings and Standards:

RMS Specification FAS/5 specifies that the illuminated flashing arrow signs shall comply with all the requirements of AS 4192:2006, except as varied in FAS/5.

D) Conditions of use:

Certificate users shall verify with RMS whether this certificate is current, valid, and applies to the latest RMS specification version, when using in situations where current validity is required.

The Type A illuminated flashing arrow sign board is designed for use in Region A, Terrain Category 2 and a maximum viewing distance of 500m.

E) Related Certification History:

Certificate Number	Issued	EV Number	Description or change details
1602-FAS5-0-1A	24/02/2016		1602-FAS5-0-1A has been renewed and superseded by this certificate.