



- NOTES:**
1. A MINIMUM OF 3 THREADS TO PROTRUDE OUT OF NUT.
 2. THE TOTAL FOOTING DEPTH OF 500mm MAY NEED TO BE INCREASED FOR POSTS INSTALLED IN UNPAVED AREAS WITH UNSTABLE SOILS.
 3. A PRE-CAST CONCRETE FOOTING MAY BE USED IN SPECIAL SITUATIONS, SUCH AS IN MEDIANS, ETC. THE CONDITION OF USE OF PRE-CAST FOOTINGS SHALL BE SUBJECT TO THE RMS REPRESENTATIVE'S AGREEMENT TO ENSURE THE PRE-CAST BLOCK IS OF THE CORRECT SIZE AND IS SITTING ON A LEVEL BASE OF SAND WITH A 14:1 MIXTURE OF SAND AND CEMENT, WELL COMPACTED AROUND THE ENTIRE BLOCK. THE PROPOSED USE OF SUCH A PRE-CAST FOOTING SHALL CONSTITUTE A 'HOLD POINT'.

A ORIGINAL ISSUE B ISSUE 13-12-2017 NOTE 3 RE USE OF PRE-CAST FOOTING ADDED. IH BWT	REFERENCE DRAWINGS Type 13 Post VM202-20 Holding Down Bolt VC002-67		ROADS AND MARITIME SERVICES TRAFFIC SIGNALS		SCALE NTS	APPROVED: 24-11-10 S. SRIVASTAVA MANAGER EQUIPMENT & STDS
	ALTERNATIVE FOOTING FOR TYPE 13 PB POST WITH EXPOSED BASE PLATE ON FINAL SURFACE			SUPERSEDES:		ISSUE A B
				DRAWN A.K. CHECKED B.W.T. PASSED B. TAYLOR 24-11-10	VC002-78	