

FACILITY	REQUIRED CONDUIT LENGTH (MEASURED FROM THE POINT OF ENTRY TO THE EQUIPMENT)	REQUIRED EXCESS LEAD OR CABLE LENGTH (MEASURED FROM THE END OF THE CONDUIT)
PEDESTRIAN LANTERN	2.3 METRE	0.7 METRE
VEHICLE LANTERN 200mm 3- OR 4-ASPECT COLUMN-MOUNTED	2.3 METRE	5 OR 6 CORE CABLE 2.2 METRE (4.5m FROM POINT OF ENTRY)
VEHICLE LANTERN 200mm 3- OR 4-ASPECT OUTREACH-MOUNTED	2.3 METRE	5 OR 6 CORE CABLE 12.7 METRE (15m FROM POINT OF ENTRY)
VEHICLE LANTERN 300mm 3-ASPECT OUTREACH-MOUNTED	2.3 METRE	5 CORE CABLE 12.7 METRE (15m FROM POINT OF ENTRY)
AUDIO-TACTILE HOUSING	2.3 METRE	0.7 METRE FOR ALL LEADS EXCEPT 4.5 METRE FOR TRANSDUCER LEADS (ie FIGURE 8 WIRES)

A ORIGINAL ISSUE B Issue 05-3-13 Flex conduit length standardised at 2.3m. Excess lead length was 1.5m. Details of 5 or 6 core cable lengths added. LC. BWT.			REFERENCE DRAWINGS							
ROADS AND TRAFFIC AUTHORITY OF NSW TRAFFIC SIGNALS		SCALE		APPROVED: 13/03/98 T YUNG						
TABLE SHOWING CONDUIT AND EXCESS LEAD LENGTHS FOR LANTERNS AND AUDIO- TACTILE HOUSING ON MULTIFUNCTION POLES		SUPERSEDES: -		MANAGER EQUIPMENT & STDS						
		DRAWN	RVC 12-03-98	ISSUE	<input checked="" type="checkbox"/> A	<input type="checkbox"/> B	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
		CHECKED	BWT 12-03-98		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
PASSED	B TAYLOR 12-03-98	VR007-7								