


NOTES

1. TOLERANCE OF ALL DIMENSIONS UNLESS OTHERWISE INDICATED:

- UP TO AND INCLUDING 100mm TO BE $\pm 0.5\text{mm}$.
- OVER 100mm TO BE $\pm 1\text{mm}$.
- ANGULAR TOLERANCE $\pm 1^\circ$.

TOLERANCE OF THE FLAT STEEL OF BRACKET TO COMPLY WITH AS/NZS 3679.

- 2. ALL BURRS, SHARP EDGES AND WELDING SCALE TO BE REMOVED BEFORE GALVANISING.
- 3. BRACKET TO BE HOT DIP GALVANISED IN ACCORDANCE WITH AS/NZS 4680.
- 4. ITEMS 2 TO 5 TO BE SUPPLIED FULLY ASSEMBLED AS SHOWN.



DIMENSIONS ARE IN MILLIMETRES

5	HEX NUT M10 TO AS/NZS 1112	MILD STEEL	GALV TO AS 1214	2
4	SPRING WASHER M10 TO AS 1968	SPRING STEEL	GALV TO AS/NZS 4680	2
3	FLAT WASHER M10 LARGE SERIES TO AS 1237	MILD STEEL	GALV TO AS/NZS 4680	2
2	CUP HD SQUARE NECK BOLT M10 X 30 TO AS/NZS 1390	MILD STEEL	GALV TO AS/NZS 4680	2
1	BRACKET 40 x 6 FLAT TO AS/NZS 3679	MILD STEEL	GALV TO AS/NZS 4680	TO SUIT
ITEM	DESCRIPTION	MATERIAL	FINISH	QTY

A ORIGINAL ISSUE

SUPPLY CAT NO
35026898

REFERENCE DRAWINGS	
BKT SINGLE MOUNT	VT006-51
BKT SINGLE LARGE	VT006-52
BKT DOUBLE SMALL	VT006-53
BKT DOUBLE MEDIUM	VT006-54
BKT DOUBLE LARGE	VT006-55

ROADS AND TRAFFIC AUTHORITY OF NSW
TRAFFIC SIGNALS

**BRACKET SINGLE END MOUNTED
FOR 450mm HIGH SPECIAL STOP SIGNS**

SCALE 1 : 5 UNLESS SHOWN OTHERWISE	
SUPERSEDES: -	
DRAWN	RVC 13-09-2000
CHECKED	BWT 02-07-2002
PASSED	BWT 02-07-2002

APPROVED: 02-07-2002
SUNIL SRIVASTAVA
MGR EQUIPMENT & STANDARDS

ISSUE A

VT006-61