



Register of Granular Materials

Users of Granular Materials must verify suitability before use on Transport for NSW (TfNSW) funded projects. Material listed on this register has been verified. Subsequent QA testing as per the specification still applies during supply of the material and any special conditions of registration must be observed when used on TfNSW funded projects.

Updated at: 4:45 PM 4/03/2021

Region	Supplier	Location	Suppliers' Material ID	Material Class	Traffic Category	Governing Specification	Status ¹	Valid to Date	Supplier Phone	Supplier Contact	Conditions																				
Sydney	Concrete Recyclers	Camellia	Class 2 DGB - Camellia	Class 2 DGB	C & D	3051 ED7 Rev0	Expired	4/06/2020	02 8832 7400	Scott Lawson	<p>Condition 1 - not approved for use where base course is constructed under traffic and the final wearing surface is a sprayed seal.</p> <p>Condition 2 - conditional approval granted on provision of adequate weathering prior to supply to prevent material gaining tensile strength (UCS must not be greater than 1.0MPa).</p>																				
Sydney	Boral	Widemere	Class 2 DGB - Widemere	Class 2 DGB	C & D	3051 ED7 Rev0	Conditional	30/04/2021	02 9033 4778	Simon Murcott	<p>Condition 1 - not approved for use where base course is constructed under traffic and the final wearing surface is a sprayed seal.</p> <p>Condition 2 - Pre-treatment is exempted for this product. The approved grading envelope prior to pre-treatment is shown below</p> <table border="1"> <thead> <tr> <th>Sieve (mm)</th> <th>% Passing</th> </tr> </thead> <tbody> <tr><td>26.5</td><td>100</td></tr> <tr><td>19</td><td>95 - 100</td></tr> <tr><td>13.2</td><td>78 - 91</td></tr> <tr><td>9.5</td><td>63 - 82</td></tr> <tr><td>4.75</td><td>44 - 62</td></tr> <tr><td>2.36</td><td>33 - 47</td></tr> <tr><td>0.425</td><td>14 - 24</td></tr> <tr><td>0.075</td><td>7 - 12</td></tr> <tr><td>0.0135</td><td>3 - 6</td></tr> </tbody> </table>	Sieve (mm)	% Passing	26.5	100	19	95 - 100	13.2	78 - 91	9.5	63 - 82	4.75	44 - 62	2.36	33 - 47	0.425	14 - 24	0.075	7 - 12	0.0135	3 - 6
Sieve (mm)	% Passing																														
26.5	100																														
19	95 - 100																														
13.2	78 - 91																														
9.5	63 - 82																														
4.75	44 - 62																														
2.36	33 - 47																														
0.425	14 - 24																														
0.075	7 - 12																														
0.0135	3 - 6																														
Southern	Boral	Dunmore	DGB20-Dunmore	Class 1 DGB	B, C & D	3051 ED7 Rev0	Conforming	31/07/2021	02 9033 4778	Simon Murcott																					
Sydney	ECORR	Wetherill Park	20DGB	Class 2 DGB	C & D	3051 ED7 Rev0	Conditional	31/07/2021	02 9757 3210	Nicole Pearce	<p>Condition 1 - not approved for use where base course is constructed under traffic and the final wearing surface is a sprayed seal.</p>																				
Sydney	Concrete Recyclers	Camellia	HB-Concrete-Recyclers-Camellia	MB20 for R73 application	A, B, C & D	3051 ED7 Rev0 & R73	Conditional	31/07/2021	02 8832 7400	Scott Lawson	<p>Condition 1 - The maximum allowable working time of the product is 6 hrs.</p>																				
Sydney	Boral	Widemere	R73 Heavily Bound Base	MB20 for R73 application	A, B, C & D	3051 ED7 Rev0 & R73	Conditional	10/10/2021	02 9033 4778	Simon Murcott	<p>Condition 1 - In-house brick content test (process control document WROPL R-056) must be submitted to projects when supplying this material. Minimum of 1 test result must be submitted for each certified stockpile (max 4000t).</p> <p>Condition 2 - Acid Soluble Sulphate (T219) test limit of up to 0.5% is accepted for this product.</p> <p>Condition 3 - Pre-treatment is exempted for this product. The approved grading envelope prior to pre-treatment is shown below:</p> <table border="1"> <thead> <tr> <th>Sieve (mm)</th> <th>% Passing</th> </tr> </thead> <tbody> <tr><td>26.5</td><td>100</td></tr> <tr><td>19</td><td>95 - 100</td></tr> <tr><td>13.2</td><td>70 - 89</td></tr> <tr><td>9.5</td><td>60 - 79</td></tr> <tr><td>2.36</td><td>30 - 48</td></tr> <tr><td>0.425</td><td>10 - 24</td></tr> <tr><td>0.075</td><td>4 - 10</td></tr> </tbody> </table>	Sieve (mm)	% Passing	26.5	100	19	95 - 100	13.2	70 - 89	9.5	60 - 79	2.36	30 - 48	0.425	10 - 24	0.075	4 - 10				
Sieve (mm)	% Passing																														
26.5	100																														
19	95 - 100																														
13.2	70 - 89																														
9.5	60 - 79																														
2.36	30 - 48																														
0.425	10 - 24																														
0.075	4 - 10																														

Note 1: Refer to website for definition of terms.



Register of Granular Materials

Users of Granular Materials must verify suitability before use on Transport for NSW (TfNSW) funded projects. Material listed on this register has been verified. Subsequent QA testing as per the specification still applies during supply of the material and any special conditions of registration must be observed when used on TfNSW funded projects.

Updated at: 4:45 PM 4/03/2021

Region	Supplier	Location.	Suppliers' Material ID	Material Class	Traffic Category	Governing Specification	Status ¹	Valid to Date	Supplier Phone	Supplier Contact	Conditions																
Sydney	Boral	Widemere	Enviroblend	MB20	A, B, C & D	3051 ED7 Rev0	Conditional	10/10/2021	02 9033 4778	Simon Murcott	<p>Condition 1 - In-house brick content test (process control document WROPL R-056) must be submitted to projects when supplying this material. Minimum of 1 test result must be submitted for each certified stockpile (max 4000t).</p> <p>Condition 2 - Acid Soluble Sulphate (T219) test limit of up to 0.5% is accepted for this product.</p> <p>Condition 3 - Pre-treatment is exempted for this product. The approved grading envelope prior to pre-treatment is shown below:</p> <table border="1"> <thead> <tr> <th>Sieve (mm)</th> <th>% Passing</th> </tr> </thead> <tbody> <tr> <td>26.5</td> <td>100</td> </tr> <tr> <td>19</td> <td>95 - 100</td> </tr> <tr> <td>13.2</td> <td>70 - 89</td> </tr> <tr> <td>9.5</td> <td>60 - 79</td> </tr> <tr> <td>2.36</td> <td>30 - 48</td> </tr> <tr> <td>0.425</td> <td>10 - 24</td> </tr> <tr> <td>0.075</td> <td>4 - 10</td> </tr> </tbody> </table>	Sieve (mm)	% Passing	26.5	100	19	95 - 100	13.2	70 - 89	9.5	60 - 79	2.36	30 - 48	0.425	10 - 24	0.075	4 - 10
Sieve (mm)	% Passing																										
26.5	100																										
19	95 - 100																										
13.2	70 - 89																										
9.5	60 - 79																										
2.36	30 - 48																										
0.425	10 - 24																										
0.075	4 - 10																										
South West	Mawsons Concrete & Quarries	Fuzzards & Berrigan	DGS20F/63	DGS20	A, B, C & D	3051 ED7 Rev0	Conforming	10/10/2021	0411 529 541	Jayden Bosch																	

Note 1: Refer to website for definition of terms.